

TOWING 2003

Compiled by Chris Hemer

You'll notice that we have excluded passenger-car tow ratings from this year's list (since very few are rated to tow more than 2,000 pounds), as well as some less-popular vehicle models. As usual, vehicles not capable of towing at least 2,000 pounds are excluded from the towing guide.

Every effort has been made to ensure the accuracy of all ratings, but because our information is often preliminary at the time of publication, some numbers may have changed by the time you visit the dealer's showroom. When in doubt, consult the manufacturer's towing guide (available at the dealership) or the vehicle owner's manual to be certain.

Acura

Vehicle	Engine	Tow Limit (lb)
Acura RL	3.5L V-6	2,000
Acura MDX	3.5L V-6	4,500 ^b

a=Requires automatic transmission and power-steering coolers when towing more than 2,000 lb. b=Maximum rated capacity of 4,500 lb is for towing boats; 3,500 lb for towing other trailers.

BMW

Vehicle	Engine	Tow Limit (lb)
BMW X5 4.6is	4.6L V-8	6,000 ^{a,b,c}
BMW X5	4.4L V-8	6,000 ^{a,b,c}
BMW X5	3.0L I-6	6,000 ^{a,b}

a=Maximum towing weight for trailers without brakes is 1,650 lb. b=Maximum towing weight for trailers with brakes off-road, 3,300 lb. c=With automatic transmission.

Buick

Vehicle	Engine	Tow Limit (lb)
Rendezvous	3.4L V-6	3,500

a=Requires towing package.

Cadillac

Vehicle	Engine	Tow Limit (lb)
Escalade 2WD	5.3L V-8	7,300
Escalade AWD	6.0L V-8	7,800
Escalade ESV	6.0L V-8	7,400
Escalade EXT	6.0L V-8	7,400

Chevrolet/GMC

Vehicle	Engine	Tow Limit (lb)
Astro/Safari and Venture Minivans		
RWD CV	4.3L V-6	5,300
RWD CV	4.3L V-6	5,800
RWD PV	4.3L V-6	4,900
RWD PV	4.3L V-6	5,400
AWD CV	4.3L V-6	5,100
AWD CV	4.3L V-6	5,600
AWD PV	4.3L V-6	4,600
AWD PV	4.3L V-6	5,100
Venture	3.4L V-6	3,500

Express/Savana

G1500 CV	4.3L V-6	4,400
G1500 CV	5.3L V-8	6,400 ^b
G1500 CV AWD	5.3L V-8	6,600 ^b
G1500 PV	4.3L V-6	4,000
G1500 PV	5.3L V-8	6,400 ^b
G1500 PV AWD	5.3L V-8	6,200 ^b
G2500 CV	4.3L V-6	4,700

G2500 CV	4.8L V-8	6,300
G2500 CV	4.8L V-8	7,300
G2500 CV	5.3L V-8	6,600
G2500 CV	6.0L V-8	8,300
G2500 CV	6.0L V-8	10,000
G2500 CV AWD	5.3L V-8	6,400
G2500 CV LWB	4.3L V-6	4,500
G2500 CV LWB	4.8L V-8	6,100
G2500 CV LWB	4.8L V-8	7,100
G2500 CV LWB	5.3L V-8	6,400
G2500 CV LWB	6.0L V-8	8,100
G2500 CV LWB	6.0L V-8	10,000
G2500 PV	6.0L V-8	7,900
G2500 PV	6.0L V-8	9,900
G2500 PV LWB	6.0L V-8	7,600
G2500 PV LWB	6.0L V-8	9,600
G3500 CV	6.0L V-8	8,300
G3500 CV	6.0L V-8	10,000
G3500 CV LWB	6.0L V-8	8,100
G3500 CV LWB	6.0L V-8	10,000
G3500 PV	6.0L V-8	7,700
G3500 PV	6.0L V-8	9,700
G3500 PV LWB	6.0L V-8	7,400
G3500 PV LWB	6.0L V-8	9,400

LWB=Long wheelbase; PV=Passenger van; CV=Cargo van; AWD=All-wheel drive; a=3.42:1 axle ratio; b=3.73:1 axle ratio; c=4.10:1 axle ratio; d=Requires heavy-duty tow package.

Blazer/Jimmy

2-Door 2WD	4.3L V-6	5,700 ^d
2-Door 2WD	4.3L V-6	4,200 ^d
Blazer Xtreme 2-Door 2WD	4.3L V-6	2,000 ^d
4-Door 2WD	4.3L V-6	5,500 ^d
2-Door 4WD	4.3L V-6	3,900 ^d
2-Door 4WD	4.3L V-6	5,400 ^{d/e}
Blazer ZR2	4.3L V-6	4,700 ^e
Blazer ZR2	4.3L V-6	4,200 ^e
4-Door 4WD	4.3L V-6	5,000 ^{d/e}

S-10 and Sonoma

Regular Cab	2.2 I-4	3,100 ^f
Regular Cab	4.3L V-6	3,900 ^e
Regular Cab	4.3L V-6	5,900 ^d
Regular Cab LB	4.3L V-6	3,900
Regular Cab LB	4.3L V-6	5,900 ^d
Extended Cab	2.2 I-4	2,000 ^f
Extended Cab	2.2 I-4	3,000 ^f
Extended Cab	4.3L V-6	3,800 ^e
Extended Cab	4.3L V-6	5,600 ^d
Extended Cab 4WD	4.3L V-6	4,000 ^d
Extended Cab 4WD	4.3L V-6	5,500 ^{d/e}
S-10 ZR2	4.3L V-6	4,200 ^e
S-10 ZR2	4.3L V-6	4,700 ^e
Crew Cab 4WD	4.3L V-6	5,200 ^{d/e}

a=Automatic transmission; b=Manual transmission; c=3.08:1 rear-axle ratio; d=3.42:1 rear-axle ratio; e=3.73:1 rear-axle ratio; f=4.10:1 rear-axle ratio.

Avalanche 1500/2500		
1500	5.3L V-8	7,200
1500	5.3L V-8	8,200
2500	8.1L V-8	10,200
2500	8.1L V-8	12,000
1500 4WD	5.3L V-8	7,000
1500 4WD	5.3L V-8	7,900
2500 4WD	8.1L V-8	9,900
2500 4WD	8.1L V-8	11,900

Sierra/Silverado Light Duty, Automatic Transmission, Conventional/Fifth-Wheel Towing (Automatic or Manual with 6.0L V-8)		
1500	4.3L V-6	4,500/NA
1500	4.3L V-6	5,000/NA
1500	4.8L V-8	6,400
1500	4.8L V-8	7,400
1500	5.3L V-8	7,400
1500	5.3L V-8	8,400
1500 LB	4.3L V-6	4,400/NA
1500 LB	4.3L V-6	4,900/NA
1500 LB	4.8L V-8	6,300
1500 LB	4.8L V-8	7,300
1500 LB	5.3L V-8	7,300
1500 LB	5.3L V-8	8,300
1500EC	4.3L V-6	4,700/NA
1500EC	4.3L V-6	5,200/NA
1500EC	4.8L V-8	6,100
1500EC	4.8L V-8	7,100
1500EC	5.3L V-8	7,100
1500EC	5.3L V-8	8,100/8,000d
Silverado SS	6.0L V-8	7,500
1500 EC AWS	5.3L V-8	7,600/7,500d
1500 EC AWS	5.3L V-8	8,600/7,500e
1500 LB EC	4.8L V-8	5,900
1500 LB EC	4.8L V-8	6,900
1500 LB EC	5.3L V-8	6,900
1500 LB EC	5.3L V-8	7,900
1500 CC	6.0L V-8	8,200
1500 CC	6.0L V-8	10,200
1500 CC AWS	6.0L V-8	7,900
1500 CC AWS	6.0L V-8	9,900
2500 LB	6.0L V-8	8,700
2500 LB	6.0L V-8	10,700
1500 4WD	4.3L V-6	4,700/NA
1500 4WD	4.3L V-6	5,200/NA
1500 4WD	4.8L V-8	7,100
1500 4WD	4.8L V-8	8,100/7,900e
1500 4WD	5.3L V-8	8,100/7,900d
1500 4WD	5.3L V-8	9,100/7,900e
1500 4WD EC	4.8L V-8	6,800
1500 4WD EC	4.8L V-8	7,800/7,700e
1500 4WD EC	5.3L V-8	7,800/7,700d

1500 4WD EC	5.3L V-8	8,800/7,700e
1500 4WD EC AWS	5.3L V-8	7,400
1500 4WD EC AWS	5.3L V-8	8,400/8,000e
Sierra Denali	6.0L V-8	10,000/9,200e
1500 4WD CC	6.0L V-8	7,900
1500 4WD CC	6.0L V-8	9,900
1500 4WD LB	4.3L V-6	4,600/NA
1500 4WD LB	4.3L V-6	5,100/NA
1500 4WD LB	4.8L V-8	7,000
1500 4WD LB	4.8L V-8	8,000
1500 4WD LB	5.3L V-8	8,000
1500 4WD LB	5.3L V-8	9,000/8,900e
1500 4WD LB EC	4.8L V-8	6,700
1500 4WD LB EC	4.8L V-8	7,700/6,800e
1500 4WD LB EC	5.3L V-8	7,700/6,800d
1500 4WD LB EC	5.3L V-8	8,700/6,800e
2500 4WD EC	6.0L V-8	8,200
2500 4WD EC	6.0L V-8	10,200

Sierra/Silverado Light Duty, Manual Transmission, Conventional Towing		
1500	4.3L V-6	3,500
1500	4.3L V-6	4,000
1500	4.8L V-8	4,400
1500	4.8L V-8	5,400
1500 EC	4.3L V-6	3,700
1500EC	4.8L V-8	4,100
1500EC	4.8L V-8	5,100
1500 LB	4.3L V-6	3,400
1500 LB	4.3L V-6	3,900
1500 LB	4.8L V-8	4,300
1500 LB	4.8L V-8	5,300
1500 LB EC	4.8L V-8	3,900
1500 LB EC	4.8L V-8	4,900
2500 LB	6.0L V-8	8,700
2500 LB	6.0L V-8	10,700
1500 4WD	4.3L V-6	3,700
1500 4WD	4.3L V-6	4,200
1500 4WD	4.8L V-8	5,100
1500 4WD	4.8L V-8	6,100
1500 4WD EC	4.8L V-8	4,800
1500 4WD EC	4.8L V-8	5,800
1500 4WD LB	4.3L V-6	3,600
1500 4WD LB	4.3L V-6	4,100
1500 4WD LB	4.8L V-8	5,000
1500 4WD LB	4.8L V-8	6,000
1500 4WD LB EC	4.8L V-8	4,700
1500 4WD LB EC	4.8L V-8	5,700
2500 4WD EC	6.0L V-8	8,200
2500 4WD EC	6.0L V-8	10,200

*2500 light duty with 8,600-lb gvwr.

Sierra/Silverado Heavy Duty, Automatic or Manual Transmission, Conventional/ Fifth-Wheel Towing		
2500 EC	6.0L V-8	10,300
2500 EC	8.1L V-8	12,000e/13,800d 15,800e
2500 EC	6.6L TD	12,000/15,700d
2500 CC	6.0L V-8	10,100
2500 CC	8.1L V-8	12,000e/13,600 d/15,600e
2500 CC	6.6L TD	12,000/15,400d
2500 LB	6.0L V-8	10,600
2500 LB	8.1L V-8	12,000e/14,100d/ 16,100e
2500 LB	6.6L V-8	12,000/16,000d
2500 LB EC	6.0L V-8	10,200
2500 LB EC	8.1L V-8	12,000e/ 3,700d/15,700e
2500 LB EC	6.6L TD	12,000/15,500d
2500 LB CC	6.0L V-8	9,900
2500 LB CC	8.1L V-8	12,000e/13,500d/ 15,500e
2500 LB CC	6.6L V-8	12,000/15,200d
3500 LB EC	6.0L V-8	9,800
3500 LB EC	8.1L V-8	12,000/15,400e
3500 LB EC	6.6L TD	12,000/15,200d
3500 LB CC	6.0L V-8	9,500
3500 LB CC	8.1L V-8	12,000/15,100e
3500 LB CC	6.6L TD	12,000/15,000d
2500 4WD EC	6.0L V-8	10,100
2500 4WD EC	8.1L V-8	12,000e/13,600d 15,600e
2500 4WD EC	6.6L TD	12,000/15,400d
2500 4WD CC	6.0L V-8	9,800
2500 4WD CC	8.1L V-8	12,000e/13,300d/ 15,300e
2500 4WD CC	6.6L TD	12,000/14,700d
2500 4WD LB	6.0L V-8	10,300
2500 4WD LB	8.1L V-8	12,000e/13,800d/ 15,800e
2500 4WD LB	6.6L TD	12,000/15,700d
2500 4WD LB EC	6.0L V-8	9,900
2500 4WD LB EC	8.1L V-8	12,000e/13,400d/ 15,400e
2500 4WD LB EC	6.6L TD	12,000/15,300d
2500 4WD LB CC	6.0L V-8	9,600
2500 4WD LB CC	8.1L V-8	12,000e/13,200d/ 14,700e
2500 4WD LB CC	6.6L TD	12,000/13,700d
3500 4WD LB	6.0L V-8	9,900
3500 4WD LB	8.1L V-8	12,000/15,500e
3500 4WD LB	6.6L TD	12,000/15,400d
3500 4WD LB EC	6.0L V-8	9,500
3500 4WD LB EC	8.1L V-8	12,000/15,100e
3500 4WD LB EC	6.6L TD	12,000/14,900d

3500 4WD LB CC	6.0L V-8	9,200
3500 4WD LB CC	8.1L V-8	12,000e/14,800e
3500 4WD LB CC	6.6L TD	12,000/14,700d

Tahoe/Yukon/Suburban/Yukon XL		
Tahoe/Yukon 1500	4.8L V-8	5,700
Tahoe/Yukon 1500	4.8L V-8	6,700
Tahoe/Yukon 1500	5.3L V-8	6,700
Tahoe/Yukon 1500	5.3L V-8	7,700
Suburban/Yukon XL 1500	5.3L V-8	7,400
Suburban/Yukon XL 1500	5.3L V-8	8,400
Tahoe/Yukon 1500 4WD	4.8L V-8	6,400
Tahoe/Yukon 1500 4WD	4.8L V-8	7,400
Tahoe/Yukon 1500 4WD	5.3L V-8	7,400e
Yukon Denali 1500 AWD	6.0L V-8	8,000
Suburban/Yukon XL 1500 4WD	5.3L V-8	7,100
Suburban/Yukon XL 1500 4WD	5.3L V-8	8,100
Yukon XL Denali 1500 AWD	6.0L V-8	7,800
Suburban/Yukon XL 2500	6.0L V-8	7,900
Suburban/Yukon XL 2500	6.0L V-8	9,900
Suburban/Yukon XL 2500	8.1L V-8	10,400
Suburban/Yukon XL 2500	8.1L V-8	12,000
Suburban/Yukon XL 2500 AWS	6.0L V-8	7,600
Suburban/Yukon XL 2500 AWS	6.0L V-8	9,600
Suburban/Yukon XL 2500 4WD	6.0L V-8	7,600
Suburban/Yukon XL 2500 4WD	6.0L V-8	9,600
Suburban/Yukon XL 2500 4WD	8.1L V-8	10,400
Suburban/Yukon XL 2500 4WD	8.1L V-8	12,000
Suburban/Yukon XL 2500 4WD AWS	6.0L V-8	7,300
Suburban/Yukon XL 2500 4WD AWS	6.0L V-8	9,300

TD=Turbodiesel; 4WD=Four-wheel drive; EC=Extended cab; CC=Crew cab; LB=Longbed; AWS=All-wheel steering; 3.08:1 axle ratio; b=3.23:1 axle ratio; c=3.42:1 axle ratio; d=3.73:1 axle ratio; e=4.10:1 axle ratio.

Manufacturer's note: Weight-distributing hitch and sway control required over 5,000 lb of trailer weight on light-duty models, 7,500 lb on heavy-duty models. Trailer ratings are calculated assuming a standard-equipped vehicle plus driver. Optional equipment, passengers or cargo will reduce trailering capacity. 1500 Series models with 4.3-liter V-6 or 4.8-liter V-8 and manual transmission are not rated to tow fifth-wheel or gooseneck trailers. 1500-series models require Z85 Increased-Capacity or ZX3 Manual Select Damping-Suspension Package to tow fifth-wheel or gooseneck trailers.

SSR		
1500 2WD	5.3L V-8	2,500

Chevrolet Trailblazer/GMC Envoy		
2WD	4.2L I-6	5,300a
2WD	4.2L I-6	5,800b
2WD	4.2L I-6	6,300c
4WD/AWD	4.2L I-6	5,200a
4WD/AWD	4.2L I-6	5,700b
4WD/AWD	4.2L I-6	6,200c

Chevrolet Trailblazer EXT/GMC Envoy XL		
2WD	4.2L I-6	4,900a

2WD	4.2L I-6	5,400
2WD	4.2L I-6	5,900
2WD	5.3L V-8	5,800
2WD	5.3L V-8	7,200
4WD/AWD	4.2L I-6	4,800
4WD/AWD	4.2L I-6	5,300
4WD/AWD	4.2L I-6	5,800
4WD/AWD	5.3L V-8	5,700
4WD/AWD	5.3L V-8	7,000

a=3.42:1 axle ratio b=3.73:1 axle ratio c=4:10:1 axle ratio

Manufacturer's note: Weight-distributing hitch and sway control required when towing over 4,000 lb of trailer weight.

DaimlerChrysler

Chrysler/Dodge		
Vehicle	Engine	Tow Limit (lb)
Dodge Caravan	3.3L, 3.8L V-6	3,800
Dodge Caravan (AWD)	3.8L V-6	3,500
Town & Country	3.3L, 3.8L V-6	3,800
Town & Country (AWD)	3.8L V-6	3,500
Voyager	3.3L V-6	2,000

Dakota		
Dakota	3.9L V-6	3,650 ^e
Dakota	3.9L V-6	3,550 ^{e*}
Dakota	3.9L V-6	4,150 ^f
Dakota	3.9L V-6	4,050 ^{f*}
Dakota	3.9L V-6	4,950 ^f
Dakota	3.9L V-6	5,350 ^h
Dakota	4.7L V-8	5,300 ^f
Dakota	4.7L V-8	5,600 ^{f*}
Dakota	4.7L V-8	6,300 ^h
Dakota	4.7L V-8	6,600 ^{h*}
Dakota	4.7L V-8	5,300 ^f
Dakota	4.7L V-8	6,600 ^h
Dakota	4.7L V-8	6,300 ^{h*}

* Denotes 5,900-lb gwwr rating. All other ratings are for 5,000-lb gwwr models.

Dakota 4WD	3.9L V-6	3,950 ^f
Dakota 4WD	3.9L V-6	3,850 ^{f*}
Dakota 4WD	3.9L V-6	4,750 ^h
Dakota 4WD	3.9L V-6	4,650 ^{h*}
Dakota 4WD	3.9L V-6	5,100 ^h
Dakota 4WD	3.9L V-6	5,050 ^{h*}
Dakota 4WD	4.7L V-8	5,400 ^f
Dakota 4WD	4.7L V-8	5,300 ^{f*}
Dakota 4WD	4.7L V-8	6,400 ^h
Dakota 4WD	4.7L V-8	6,300 ^{h*}
Dakota 4WD	4.7L V-8	5,000 ^f
Dakota 4WD	4.7L V-8	4,950 ^{f*}
Dakota 4WD	4.7L V-8	6,300 ^h
Dakota 4WD	4.7L V-8	6,250 ^{h*}

* Denotes 5,900-lb gwwr rating. All other ratings are for 5,000-lb gwwr models.

Dakota Club Cab	3.9L V-6	3,500 ^e
Dakota Club Cab	3.9L V-6	4,000 ^f
Dakota Club Cab	3.9L V-6	3,900 ^{f*}
Dakota Club Cab	3.9L V-6	4,700 ^f
Dakota Club Cab	3.9L V-6	5,100 ^h
Dakota Club Cab	3.9L V-6	5,050 ^{h*}
Dakota Club Cab	4.7L V-8	5,300 ^f
Dakota Club Cab	4.7L V-8	6,300 ^h
Dakota Club Cab	4.7L V-8	5,000 ^f
Dakota Club Cab	4.7L V-8	6,300 ^h

* Denotes 6,010-lb gwwr rating, except models with California emissions. All other ratings are for 5,350-lb gwwr models.

Dakota Club Cab 4WD	3.9L V-6	3,600 ^f
Dakota Club Cab 4WD	3.9L V-6	4,400 ^h
Dakota Club Cab 4WD	3.9L V-6	4,800 ^h
Dakota Club Cab 4WD	4.7L V-8	5,050 ^f
Dakota Club Cab 4WD	4.7L V-8	6,050 ^h
Dakota Club Cab 4WD	4.7L V-8	4,750 ^f
Dakota Club Cab 4WD	4.7L V-8	6,050 ^h

Note: All of the above models have a 6,010-lb gwwr rating, except models with California emissions.

Dakota Quad Cab	3.9L V-6	3,600 ^f
Dakota Quad Cab	3.9L V-6	4,400 ^h
Dakota Quad Cab	3.9L V-6	4,400 ^f
Dakota Quad Cab	3.9L V-6	4,800 ^h
Dakota Quad Cab	4.7L V-8	5,050 ^f
Dakota Quad Cab	4.7L V-8	6,050 ^h
Dakota Quad Cab	4.7L V-8	4,750 ^f
Dakota Quad Cab	4.7L V-8	6,050 ^h
Dakota Quad Cab	5.9L V-8	4,350 ^f
Dakota Quad Cab	5.9L V-8	5,950 ^h
Dakota Quad Cab 4WD	3.9L V-6	3,400 ^f
Dakota Quad Cab 4WD	3.9L V-6	4,200 ^h
Dakota Quad Cab 4WD	3.9L V-6	4,200 ^f
Dakota Quad Cab 4WD	3.9L V-6	4,600 ^h
Dakota Quad Cab 4WD	4.7L V-8	4,800 ^f
Dakota Quad Cab 4WD	4.7L V-8	5,800 ^h
Dakota Quad Cab 4WD	4.7L V-8	4,500 ^f
Dakota Quad Cab 4WD	4.7L V-8	5,800 ^h
Dakota Quad Cab 4WD	5.9L V-8	4,350 ^f
Dakota Quad Cab 4WD	5.9L V-8	5,950 ^h

Note: All of the above models have a 6,010-lb gwwr rating, except models with California emissions.

Manufacturer's note: Maximum trailer-weight ratings for all Dakota models include cargo and fluids in the trailer and 150 lb for the driver, and must be decreased by the weight of optional equipment, trailer hitch, cargo and passengers.

Durango	4.7L V-8	4,650
Durango	4.7L V-8	5,950
Durango	5.9L V-8	5,850
Durango	5.9L V-8	7,550
Durango 4WD	4.7L V-8	4,400
Durango 4WD	4.7L V-8	5,700

Durango 4WD	5.9L V-8	5,600
Durango 4WD	5.9L V-8	7,300

Ram Van 1500

109" Wheelbase	3.9L V-6	4,450
109" Wheelbase	5.2L V-8	5,450
109" Wheelbase	5.2L V-8	5,950
127" Wheelbase	3.9L V-6	4,250
127" Wheelbase	5.2L V-8	6,750
127" Wheelbase	5.2L V-8	7,750
127" Wheelbase	5.9L V-8	7,200
127" Wheelbase	5.9L V-8	8,200
127" Wheelbase Maxi	3.9L V-6	4,150
127" Wheelbase Maxi	5.2L V-8	6,650
127" Wheelbase Maxi	5.2L V-8	7,650
127" Wheelbase Maxi	5.9L V-8	7,100
127" Wheelbase Maxi	5.9L V-8	8,100

Ram Van 2500

127" Wheelbase	3.9L V-6	4,050
127" Wheelbase	5.2L V-8	7,600
127" Wheelbase	5.2L V-8	8,100
127" Wheelbase	5.9L V-8	8,100
127" Wheelbase	5.9L V-8	8,600
127" Wheelbase Maxi	5.2L V-8	7,450
127" Wheelbase Maxi	5.2L V-8	7,950
127" Wheelbase Maxi	5.9L V-8	7,900
127" Wheelbase Maxi	5.9L V-8	8,400

Ram Van 3500

127" Wheelbase	5.2L V-8	7,550
127" Wheelbase	5.2L V-8	8,050
127" Wheelbase	5.9L V-8	8,050
127" Wheelbase	5.9L V-8	8,550
127" Wheelbase Maxi	5.2L V-8	7,400
127" Wheelbase Maxi	5.2L V-8	7,900
127" Wheelbase Maxi	5.9L V-8	7,900
127" Wheelbase Maxi	5.9L V-8	8,400

Manufacturer's note: Maximum trailer-weight ratings include cargo and fluids in the trailer and 150 lb for the driver, and must be decreased by the weight of optional equipment, trailer hitch, cargo and passengers. Load-equalizing hitch recommended for trailers over 2,000 lb.

Ram Truck 1500, Regular Cab 2WD**

1500	3.7L V-6	3,350,f/h
1500	3.7L V-6	3,750,f/h
1500	4.7L V-8	4,800,f
1500	4.7L V-8	5,800,h
1500	4.7L V-8	4,700,h*
1500	4.7L V-8	6,700,f
1500	4.7L V-8	7,700,h
1500	4.7L V-8	6,650,h*
1500	5.9L V-8	7,650,f
1500	5.9L V-8	8,650,h
1500	5.9L V-8	7,600,h*

** Ratings shown are for short box, 2WD models. Longbed models are rated to

tow 200-250 lb less (most models). 4WD models are rated to tow 250-300 lb less. Models with a longbed and 4WD are rated to tow 450-500 lb less. The 3.7-liter engine is not available with 4WD.

Ram Truck 1500 Quad Cab**

1500 Quad Cab	3.7L V-6	3,050/g
1500 Quad Cab	3.7L V-6	3,500/g
1500 Quad Cab	4.7L V-8	4,450,f
1500 Quad Cab	4.7L V-8	5,450,h
1500 Quad Cab	4.7L V-8	4,400,h*
1500 Quad Cab	4.7L V-8	6,400,f
1500 Quad Cab	4.7L V-8	7,400,h
1500 Quad Cab	4.7L V-8	6,350,h*
1500 Quad Cab	5.9L V-8	7,350,f
1500 Quad Cab	5.9L V-8	8,350,h
1500 Quad Cab	5.9L V-8	7,300,h*

** Shortbed, 2WD ratings shown. Longbed models are rated to tow 200-250 lb less (most models). 4WD models are rated to tow 250-300 lb less. Models with long bed and 4WD are rated to tow 500-550 lb less.

* With optional 20-inch wheel and tire Sport Group available on short-box models only.

Manufacturer's note: The gross trailer weight rating (gtwr) is the maximum allowable weight of the trailer and its cargo. Gtwr equals the gross combination weight rating (gcwr) minus curb weight of truck minus 150 lb (allowance for driver), and must be further decreased by the weight of optional equipment, trailer hitch, cargo and passengers. Maximum trailer weights shown are rounded to the nearest 50 lb. A weight-distributing hitch is recommended for trailers weighing more than 2,000 lb.

Ram Truck 2500 Regular Cab, Long Bed 2WD**

2500	5.7L V-8	9,550,g
2500	5.7L V-8	11,550,i
2500	5.7L V-8	9,600,d,g
2500	5.7L V-8	11,600,i
2500	8.0L V-10	11,100,g
2500	8.0L V-10	13,100,i
2500	8.0L V-10	11,150,g
2500	8.0L V-10	13,150,i
2500	5.9L TD	12,800,g
2500	5.9L TD	11,800,a,g
2500	5.9L TD	13,800,i
2500	5.9L TD	11,850,d,g
2500	5.9L TD	10,850,d,g
2500	5.9L TD	13,850,d,i
2500	5.9L TD	12,850,d,i
2500	5.9L TD HO	13,650,g/i

**Note: 4WD models are rated to tow 450 lb less.

2500 Quad Cab Shortbed, 2WD**

2500 Quad Cab	5.7L V-8	9,350,g
2500 Quad Cab	5.7L V-8	11,350,i
2500 Quad Cab	5.7L V-8	9,400,g
2500 Quad Cab	5.7L V-8	11,400,i
2500 Quad Cab	8.0L V-10	10,900,g

2500 Quad Cab	8.0L V-10	12,900
2500 Quad Cab	8.0L V-10	10,950g
2500 Quad Cab	8.0L V-10	12,950
2500 Quad Cab	5.9L TD	12,600g
2500 Quad Cab	5.9L TD	11,600a,g
2500 Quad Cab	5.9L TD	13,600
2500 Quad Cab	5.9L TD	11,650g
2500 Quad Cab	5.9L TD	10,650d,g
2500 Quad Cab	5.9L TD	13,650
2500 Quad Cab	5.9L TD	12,650d,i
2500 Quad Cab	5.9L TD HO	13,450g/i

** Ratings shown are for shortbed, 2WD models. Longbed models are rated to tow 150 lb less. 4WD models are rated to tow 500 lb less. Longbed, 4WD models are rated to tow 600 lb less.

**Ram Truck 3500
Regular Cab Longbed,
Dual Rear Wheels****

3500	5.7L V-8	11,000,i
3500	5.7L V-8	11,050d,i
3500	8.0L V-10	10,650g
3500	8.0L V-10	12,650a,i
3500	8.0L V-10	10,700d,g
3500	8.0L V-10	12,700d,i
3500	5.9L TD	12,350a,g
3500	5.9L TD	11,350a,g
3500	5.9L TD	14,350a,i
3500	5.9L TD	13,350a,i
3500	5.9L TD	11,450d,g
3500	5.9L TD	10,450d,g
3500	5.9L TD	13,450d,i
3500	5.9L TD	12,450d,i
3500	5.9L TD HO	14,200g
3500	5.9L TD HO	16,200,i

** 4WD models are rated to tow 450-500 lb less.

**3500 Quad Cab
2WD Shortbed,
Single Rear Wheels****

3500 Quad Cab	5.9L TD	12,450g
3500 Quad Cab	5.9L TD	11,450a,g
3500 Quad Cab	5.9L TD	14,450
3500 Quad Cab	5.9L TD	13,450a,i
3500 Quad Cab	5.9L TD	11,500g
3500 Quad Cab	5.9L TD	10,500d,g
3500 Quad Cab	5.9L TD	13,500
3500 Quad Cab	5.9L TD	12,500d,i
3500 Quad Cab	5.9L TD HO	14,300g
3500 Quad Cab	5.9L TD HO	16,300

** Longbed models are rated to tow 100 lb less. 4WD models are rated to tow 450 lb less. Longbed, 4WD models are rated to tow 600 lb less.

**3500 Quad Cab Longbed 2WD,
Dual Rear Wheels**

3500 Quad Cab LB	5.7L V-8	10,600
3500 Quad Cab LB	5.7L V-8	10,650

3500 Quad Cab LB	8.0L V-10	10,250
3500 Quad Cab LB	8.0L V-10	12,250
3500 Quad Cab LB	8.0L V-10	10,300
3500 Quad Cab LB	8.0L V-10	12,300
3500 Quad Cab LB	5.9L TD	12,000g
3500 Quad Cab LB	5.9L TD	11,000a,g
3500 Quad Cab LB	5.9L TD	14,000
3500 Quad Cab LB	5.9L TD	13,000a,i
3500 Quad Cab LB	5.9L TD	11,050g
3500 Quad Cab LB	5.9L TD	10,050d,g
3500 Quad Cab LB	5.9L TD	13,050
3500 Quad Cab LB	5.9L TD	12,050d,i
3500 Quad Cab LB	5.9L TD HO	13,850
3500 Quad Cab LB	5.9L TD HO	15,850

Note: 4WD models are rated to tow 450-500 lb less.

Manufacturer's note: Ratings are for ST models. Ratings for SLT models are approximately 100 lb less. A weight-distributing hitch is recommended for trailers weighing more than 2,000 lb. An exhaust brake is strongly recommended for manual-transmission applications when towing a trailer weighing more than 10,000 lb.

TD=Turbodiesel; HO=High Output; a=5-speed manual; b=6-speed manual; c=3-speed automatic; d=4- or 5-speed automatic (five-speed with 5.7L V-8 only); e=3.21 axle; f=3.55 axle; g=3.73 axle; h=3.92 axle; i=4:10 axle; j=optional Trailer-Preparation Group required.

* Denotes California emissions-equipped 5.9L 24V Cummins turbodiesel engine.

Ford

Econoline Van/Wagon

Vehicle	Engine	Tow Limit (lb)
E-150	4.2L V-6	5,000/4,700c
E-150	4.6L V-8	6,400/6,100c
E-150	5.4L V-8	6,800/6,500c
E-250	4.2L V-6	5,100/NA
E-250	4.2L V-6	5,600/NA
E-250	4.6L V-8	6,100/NA
E-250	4.6L V-8	6,000/NA
E-250	5.4L V-8	7,500/NA
E-250 NGV	5.4L V-8	6,900/NA
E-250 Ext	4.2L V-6	5,000/NA
E-250 Ext	4.2L V-6	5,400/NA
E-250 Ext	4.6L V-8	5,900/NA
E-250 Ext	4.6L V-8	5,800/NA
E-250 Ext	5.4L V-8	7,300/NA
E-250 NGV Ext	5.4L V-8	7,300/NA
E-350	5.4L V-8	6,300/NA
E-350	5.4L V-8	7,300/6,900d-e
E-350 NGV	5.4L V-8	6,700/6,300e
E-350	6.8L V-10	9,200/8,800d
E-350	6.8L V-10	10,000
E-350	7.3L TD	9,700/9,400c
E-350	7.3L TD	10,000
E-350 Ext	5.4L V-8	6,200/5,600c
E-350 Ext	5.4L V-8	7,200/6,600d-e

E-350 NGV Ext	5.4L V-8	6,600	6,000e
E-350 Ext.	6.8L V-10	9,000	8,500d
E-350 Ext.	6.8L V-10	10,000	
E-350 Ext	7.3L TD	9,600	9,100c
E-350 Ext	7.3L TD	10,000	

Excursion

Excursion	5.4L V-8	6,100	
Excursion	5.4L V-8	7,600	
Excursion	6.8L V-10	10,000	
Excursion	6.8L V-10	11,000	
Excursion	6.0L TD	11,000	d
Excursion 4WD	5.4L V-8	7,200	
Excursion 4WD	6.8L V-10	9,600	
Excursion 4WD	6.8L V-10	11,000	
Excursion 4WD	6.0L TD	11,000	d

Expedition

Expedition	4.6L V-8	6,050	
Expedition	5.4L V-8	8,900	
Expedition 4WD	4.6L V-8	5,750	
Expedition 4WD	5.4L V-8	8,650	

Explorer Sport (2dr) and Sport Trac, Manual Transmission

Explorer Sport	4.0L V-6	2,940	
Explorer Sport 4WD	4.0L V-6	2,760	
Explorer Sport Trac	4.0L V-6	2,700	
Explorer Sport Trac 4WD	4.0L V-6	2,480	

Explorer Sport (2dr) and Sport Trac, Automatic Transmission

Explorer Sport	4.0L V-6	5,000	
Explorer Sport 4WD	4.0L V-6	4,820	
Explorer Sport Trac	4.0L V-6	5,260	
Explorer Sport Trac 4WD	4.0L V-6	5,060	

Explorer 4 Door, Automatic Transmission

Explorer	4.0L V-6	3,280	(1)
Explorer	4.0L V-6	5,560	(2)
Explorer	4.0L V-6	5,800	(3)
Explorer	4.6L V-8	3,280	(1)
Explorer	4.6L V-8	7,160	(3)*
Explorer 4WD	4.0L V-6	3,400	(1)
Explorer 4WD	4.0L V-6	5,400	(2)
Explorer 4WD	4.0L V-6	5,380	(3)
Explorer 4WD	4.6L V-8	3,420	(1)
Explorer 4WD	4.6L V-8	7,000	(3)*

(1)=With Class II hitch;(2)=With Class III/IV hitch;(3)=With Class III/IV hitch and limited-slip axle.

* Deduct 500 lb with third-row seat with auxiliary climate control.

Escape

Escape	3.0L V-6	3,500	
--------	----------	-------	--

*With Class II trailer-towing package. Rating is 2,000 lb without.

F-150, Manual Transmission, Conventional Towing

Regular Cab	4.2L V-6	2,000	
Regular Cab	4.2L V-6	3,560	
Regular Cab	4.6L V-8	2,000	
Regular Cab	4.6L V-8	2,900	
Regular Cab	4.6L V-8	3,560	
Regular Cab 4WD	4.2L V-6	2,500	
Regular Cab 4WD	4.2L V-6	3,200	
Regular Cab 4WD	4.6L V-8	2,500	
Regular Cab 4WD	4.6L V-8	3,100	
SuperCab	4.2L V-6	2,000	
SuperCab	4.2L V-6	3,300	
SuperCab	4.6L V-8	2,000	
SuperCab	4.6L V-8	2,600	
SuperCab	4.6L V-8	3,200	
SuperCab 4WD	4.6L V-8	2,300	
SuperCab 4WD	4.6L V-8	2,900	

F-150, Automatic Transmission, Conventional/Fifth-Wheel Towing

Regular Cab	4.2L V-6	4,600	NA
Regular Cab	4.2L V-6	5,760	
Regular Cab	4.6L V-8	2,000	NA
Regular Cab	4.6L V-8	6,100	NA
Regular Cab	4.6L V-8	7,160	
Regular Cab	5.4L V-8	7,500	NA
Regular Cab	5.4L V-8	8,500	NA
Regular Cab	5.4L V-8	8,800	
Regular Cab	5.4L V-8	8,800	
Regular Cab NGV	5.4L V-8	5,900	NA
Regular Cab 4WD	4.2L V-6	5,300	
Regular Cab 4WD	4.6L V-8	5,800	NA
Regular Cab 4WD	4.6L V-8	6,800	
Regular Cab 4WD	4.6L V-8	6,300	
Regular Cab 4WD	5.4L V-8	7,500	NA
Regular Cab 4WD	5.4L V-8	8,500	
Regular Cab 4WD	5.4L V-8	8,800	
Regular Cab 4WD	5.4L V-8	8,800	
SuperCab	4.2L V-6	4,400	NA
SuperCab	4.2L V-6	5,400	
Super Cab	4.6L V-8	2,000	NA
Super Cab	4.6L V-8	5,800	NA
Super Cab	4.6L V-8	6,800	
SuperCab	5.4L V-8	7,200	NA
SuperCab	5.4L V-8	8,200	
SuperCab	5.4L V-8	8,500	
SuperCab	5.4L V-8	8,500	
SuperCab 4WD	4.6L V-8	5,500	NA
SuperCab 4WD	4.6L V-8	6,500	
SuperCab 4WD	4.6L V-8	6,000	
SuperCab 4WD	5.4L V-8	6,900	NA
SuperCab 4WD	5.4L V-8	7,900	

SuperCab 4WD	5.4L V-8	7,460
SuperCab 4WD	5.4L V-8	8,260
Super Crew	4.6L V-8	6,500/NA
SuperCrew	5.4L V-8	7,900/NA
Super Crew 4WD	4.6L V-8	6,200/NA
Super Crew 4WD	4.6L V-8	6,160/NA
SuperCrew 4WD	5.4L V-8	7,600/NA
SuperCrew 4WD	5.4L V-8	7,160/NA
SuperCrew 4WD	5.4L V-8	7,160/NA

**Super Duty F-250/F-350,
Manual Transmission, Conventional/
Fifth-Wheel Towing**

Regular Cab	5.4L V-8	7,860
Regular Cab	5.4L V-8	9,360
Regular Cab	6.8L V-10	10,660
Regular Cab	6.8L V-10	12,500/13,100f
Regular Cab	6.0L TD	12,500/13,600d
Regular Cab 4WD	5.4L V-8	7,460
Regular Cab 4WD	5.4L V-8	8,960
Regular Cab 4WD	6.8L V-10	10,260
Regular Cab 4WD	6.8L V-10	12,500/13,700f
Regular Cab 4WD	6.0L TD	12,500d/13,300d

Manufacturer's note: For F-250-350 single rear-wheel (SRW) models, F-350 maximum trailer weights are shown. F-250 maximum trailer weights are within 100 lb.

SuperCab	5.4L V-8	7,460
SuperCab	5.4L V-8	8,960
SuperCab	6.8L V-10	10,360
SuperCab	6.8L V-10	12,500/13,800f
SuperCab	6.0L TD	12,500d/13,300d
SuperCab 4WD	5.4L V-8	7,160
SuperCab 4WD	5.4L V-8	8,660
SuperCab 4WD	6.8L V-10	9,960
SuperCab 4WD	6.8L V-10	12,500/13,400f
SuperCab 4WD	6.0L TD	12,500d/12,900d**

**Manufacturer's note: For F-250-350 single rear-wheel (SRW) models, F-350 maximum trailer weights are shown. F-250 trailer weights are within 100 lb, except for the F-250 SRW 4WD Supercab applications indicated above. For these applications, maximum loaded-trailer weight is 12,000 lb.

Crew Cab	5.4L V-8	7,200
Crew Cab	5.4L V-8	8,700
Crew Cab	6.8L V-10	10,100
Crew Cab	6.8L V-10	12,500/13,600f
Crew Cab	6.0L TD	12,500d/12,900d
Crew Cab 4WD	5.4L V-8	6,800
Crew Cab 4WD	5.4L V-8	8,300
Crew Cab 4WD	6.8L V-10	9,700
Crew Cab 4WD	6.8L V-10	12,500/13,200f
Crew Cab 4WD	6.0L TD	12,500d/12,700d**

**Manufacturer's note: For F-250-350 single rear-wheel (SRW) models, F-

350 maximum trailer weights are shown. F-250 trailer weights are within 100 lb, except for the F-250 SRW 4WD Crew cab applications indicated above. For these applications, maximum loaded-trailer weight is 10,400 lb.

F-350 DRW	5.4L V-8	7,500
F-350 DRW	5.4L V-8	9,000
F-350 DRW	6.8L V-10	10,300
F-350 DRW	6.8L V-10	12,500/13,800f
F-350 DRW	6.8L V-10	13,800
F-350 DRW	6.0L TD	13,300d/e
F-350 4WD DRW	5.4L V-8	7,160
F-350 4WD DRW	5.4L V-8	8,660
F-350 4WD DRW	6.8L V-10	9,960
F-350 4WD DRW	6.8L V-10	12,500/13,400f
F-350 4WD DRW	6.8L V-10	13,400
F-350 4WD DRW	6.0L TD	12,900d,e
F-350 SuperCab DRW	5.4L V-8	7,200
F-350 SuperCab DRW	5.4L V-8	8,700
F-350 SuperCab DRW	6.8L V-10	10,000
F-350 SuperCab DRW	6.8L V-10	12,500/13,500f
F-350 SuperCab DRW	6.8L V-10	13,500
F-350 SuperCab DRW	6.0L TD	13,000d-e
F-350 SuperCab 4WD DRW	5.4L V-8	6,800
F-350 SuperCab 4WD DRW	5.4L V-8	8,300
F-350 SuperCab 4WD DRW	6.8L V-10	9,600
F-350 SuperCab 4WD DRW	6.8L V-10	12,500/13,100f
F-350 SuperCab 4WD DRW	6.8L V-10	13,100
F-350 SuperCab 4WD DRW	6.0L TD	12,600d-e
F-350 Crew Cab DRW	6.8L V-10	9,800
F-350 Crew Cab DRW	6.8L V-10	12,500/13,300f
F-350 Crew Cab DRW	6.8L V-10	13,300
F-350 Crew Cab DRW	6.0L TD	12,800d-e
F-350 Crew Cab 4WD DRW	6.8L V-10	9,400
F-350 Crew Cab 4WD DRW	6.8L V-10	12,500/12,900f
F-350 Crew Cab 4WD DRW	6.8L V-10	12,900
F-350 Crew Cab 4WD DRW	6.0L TD	12,400d-e

**Super Duty F-250/F-350,
Automatic Transmission, Conventional/
Fifth-Wheel Towing**

Regular Cab	5.4L V-8	7,860
Regular Cab	5.4L V-8	9,360
Regular Cab	6.8L V-10	11,260
Regular Cab	6.8L V-10	12,500/14,200f
Regular Cab	6.0L TD	12,500d/13,700d
Regular Cab 4WD	5.4L V-8	7,460
Regular Cab 4WD	5.4L V-8	8,960
Regular Cab 4WD	6.8L V-10	10,860
Regular Cab 4WD	6.8L V-10	12,500/13,800f
Regular Cab 4WD	6.0L TD	12,500d/13,300d
SuperCab	5.4L V-8	7,500
SuperCab	5.4L V-8	9,000
SuperCab	6.8L V-10	10,800
SuperCab	6.8L V-10	12,500/13,800f
SuperCab	6.0L TD	12,500d/13,300d
SuperCab 4WD	5.4L V-8	7,160

SuperCab 4WD	5.4L V-8	8,660
SuperCab 4WD	6.8L V-10	10,460
SuperCab 4WD	6.8L V-10	12,500/13,400f
SuperCab 4WD	6.0L TD	12,500d/13,000d*

*Manufacturer's note: For F-250/350 single rear-wheel (SRW) models, F-350 maximum trailer weights are shown. F-250 trailer weights are within 100 lb, except for the F-250 SRW 4WD Supercab applications indicated above. For these applications, maximum loaded-trailer weight is 12,000 lb.

Crew Cab	5.4L V-8	7,200
Crew Cab	5.4L V-8	8,700
Crew Cab	6.8L V-10	10,600
Crew Cab	6.8L V-10	12,500/13,600f
Crew Cab	6.0L TD	12,500d/13,100d
Crew Cab 4WD	5.4L V-8	6,900
Crew Cab 4WD	5.4L V-8	8,400
Crew Cab 4WD	6.8L V-10	10,200
Crew Cab 4WD	6.8L V-10	12,500/13,200f
Crew Cab 4WD	6.0L TD	12,500d/12,700d*

*Manufacturer's note: For F-250/350 single rear-wheel (SRW) models, F-350 maximum trailer weights are shown. F-250 trailer weights are within 100 lb, except for the F-250 SRW 4WD Crew cab applications indicated above. For these applications, maximum loaded-trailer weight is 10,400 lb.

F-350 DRW	5.4L V-8	7,600
F-350 DRW	5.4L V-8	9,100
F-350 DRW	6.8L V-10	10,900
F-350 DRW	6.8L V-10	12,500/13,900f
F-350 DRW	6.8L V-10	13,900
F-350 DRW	6.0L TD	13,400d-e
F-350 4WD DRW	5.4L V-8	7,200
F-350 4WD DRW	5.4L V-8	8,700
F-350 4WD DRW	6.8L V-10	10,400
F-350 4WD DRW	6.8L V-10	12,500/13,400f
F-350 4WD DRW	6.8L V-10	13,400
F-350 4WD DRW	6.0L TD	13,000d-e
F-350 SuperCab DRW	5.4L V-8	7,200
F-350 SuperCab DRW	5.4L V-8	8,700
F-350 SuperCab DRW	6.8L V-10	10,500
F-350 SuperCab DRW	6.8L V-10	12,500/13,500f
F-350 SuperCab DRW	6.8L V-10	13,500
F-350 SuperCab DRW	6.0L TD	13,000d-e
F-350 SuperCab 4WD DRW	5.4L V-8	6,800
F-350 SuperCab 4WD DRW	5.4L V-8	8,300
F-350 SuperCab DRW	6.8L V-10	10,800
F-350 SuperCab DRW	6.8L V-10	12,500/13,100f
F-350 SuperCab DRW	6.8L V-10	13,100
F-350 SuperCab 4WD DRW	6.0L TD	12,600d-e
F-350 Crew Cab DRW	6.8L V-10	10,300
F-350 Crew Cab DRW	6.8L V-10	12,500/13,300f
F-350 Crew Cab DRW	6.8L V-10	13,300
F-350 Crew Cab DRW	6.0L TD	12,800d-e
F-350 Crew Cab 4WD DRW	6.8L V-10	9,900
F-350 Crew Cab 4WD DRW	6.8L V-10	12,500/12,900f
F-350 Crew Cab 4WD DRW	6.8L V-10	12,900
F-350 Crew Cab 4WD DRW	6.0L TD	12,400d-e

Super Duty F-350/450/550 Chassis Cab,
Manual/Automatic Transmission,
Fifth-Wheel Towing

F-350 Chassis Cab

F-350	5.4L V-8	7,200/7,300d
F-350	5.4L V-8	8,700/8,800e
F-350	6.8L V-10	10,100/10,600
F-350	6.0L TD	13,100d
F-350 4WD	5.4L V-8	6,800
F-350 4WD	5.4L V-8	8,300
F-350 4WD	6.8L V-10	9,700/10,200d
F-350 4WD	6.0L TD	12,700d
F-350 DRW	5.4L V-8	6,900/7,000d
F-350 DRW	5.4L V-8	8,400/8,500e
F-350 DRW	6.8L V-10	9,700/10,300d
F-350 DRW	6.8L V-10	13,200/13,300f
F-350 DRW	6.0L TD	12,700d/e
F-350 4WD DRW	5.4L V-8	6,400
F-350 4WD DRW	5.4L V-8	7,900/8,000e
F-350 4WD DRW	6.8L V-10	9,200/9,800d
F-350 4WD DRW	6.8L V-10	12,700/12,800f
F-350 4WD DRW	6.0L TD	12,200d/e
F-350 SCC	5.4L V-8	6,900
F-350 SCC	5.4L V-8	8,400
F-350 SCC	6.8L V-10	9,700/10,300d
F-350 SCC	6.0L TD	12,700d/12,800d
F-350 4WD SCC	5.4L V-8	6,400/6,500d
F-350 4WD SCC	5.4L V-8	7,900/8,000e
F-350 4WD SCC	6.8L V-10	9,300/9,800d
F-350 4WD SCC	6.0L TD	12,300d
F-350 SCC DRW	6.8L V-10	9,400/9,900d
F-350 SCC DRW	6.8L V-10	12,900
F-350 SCC DRW	6.0L TD	12,400d-e/12,500d-e
F-350 SCC 4WD DRW	6.8L V-10	9,000/9,500d
F-350 SCC 4WD DRW	6.8L V-10	12,500
F-350 SCC 4WD DRW	6.0L TD	12,000d-e/12,100d-e
F-350 CCC	5.4L V-8	6,700
F-350 CCC	5.4L V-8	8,200
F-350 CCC	6.8L V-10	9,500/10,000d
F-350 CCC	6.0L TD	12,500d/12,600d
F-350 CCC 4WD	5.4L V-8	6,200/6,300d
F-350 CCC 4WD	5.4L V-8	7,700/7,800e
F-350 CCC 4WD	6.8L V-10	9,100/9,600d
F-350 CCC 4WD	6.0L TD	12,100d/12,200d
F-350 CCC DRW	6.8L V-10	9,200/9,700d
F-350 CCC DRW	6.8L V-10	12,700
F-350 CCC DRW	6.0L TD	12,200d-e/12,300d-e
F-350 CCC 4WD DRW	6.8L V-10	8,700/9,300d
F-350 CCC 4WD DRW	6.8L V-10	12,200/12,300f
F-350 CCC 4WD DRW	6.0L TD	11,700d-e/11,800d-e

F-450 Chassis Cab

F-450 DRW	6.8L V-10	14,500g/16,600g-h
F-450 DRW	6.0L TD	18,000f-g/18,100f-g
F-450 4WD DRW	6.8L V-10	14,200g/16,300g-h

F-450 4WD DRW	6.0L TD	17,700f-g/17,800f-g
F-450 SCC DRW	6.8L V-10	14,200/16,200g-h
F-450 SCC DRW	6.0L TD	17,700f-g
F-450 SCC 4WD DRW	6.8L V-10	13,800/15,800g-h
F-450 SCC 4WD DRW	6.0L TD	17,300f-g
F-450 CCC DRW	6.8L V-10	14,000h/16,000g-h
F-450 CCC DRW	6.0L TD	17,500f-g
F-450 CCC 4WD DRW	6.8L V-10	13,700/15,700g-h
F-450 CCC 4WD DRW	6.0L TD	17,200f-g

F-550 Chassis Cab

F-550 DRW	6.8L V-10	14,500h/16,500g-h
F-550 DRW	6.0L TD	18,000g
F-550 4WD DRW	6.8L V-10	14,100h/16,200g-h
F-550 4WD DRW	6.0L TD	17,700g/17,600g
F-550 SCC DRW	6.8L V-10	14,100/16,200g-h
F-550 SCC DRW	6.0L TD	17,600g/17,700g
F-550 SCC 4WD DRW	6.8L V-10	13,700/15,700g-h
F-550 SCC 4WD DRW	6.0L TD	17,200g
F-550 CCC DRW	6.8L V-10	13,900h/15,900g-h
F-550 CCC DRW	6.0L TD	17,400g/21,400g*
F-550 CCC 4WD DRW	6.8L V-10	13,600/15,600g,h
F-550 CCC 4WD DRW	6.0L TD	17,000g/17,100g

Manufacturer's note A: Trailer weights for all Chassis cab models assume a 1,000-lb second-unit body weight. Be sure combined weight of vehicle and trailer does not exceed the gross combination weight rating (gcwr).

Manufacturer's note B: F-450/550 weights shown are for 141-inch-wheelbase Regular cab or 176-inch-wheelbase Crew cab models. For 165-, 189-, 200- and 201-inch-wheelbase models, weights may be somewhat less (usually not more than 400 lb).

* Available with high-capacity trailer-tow package only.

Super Duty F-650/750, All Models/ Powertrains

Model	Max gvwr	Max gcwr
F-650 Super Crewzer	23,000 lb	43,000-lb gcwr
F-650 Regular/SC/CC	26,000 lb	40,000-lb gcwr
F-750 Regular/SC/CC	30,000 lb	45,000-lb gcwr
F-750 Regular/SC/CC	33,000 lb	60,000-lb gcwr

* To determine maximum trailer weight, subtract your vehicle's gvwr from the maximum gcwr.

Ranger, Manual/ Automatic Transmission

Ranger SB	2.3L I-4	NA/2,240
Ranger SB	3.0L V-6	2,600/2,100d
Ranger SB	3.0L V-6	2,500(1)/4,000e(1)
Ranger SB 4WD	3.0L V-6	2,360/2,820e
Ranger LB	3.0L V-6	2,500/2,040d
Ranger SuperCab	3.0L V-6	2,400/2,940d
Ranger SuperCab	3.0L V-6	2,340(1)/3,800e(2)
Ranger SuperCab	4.0L V-6	3,280(1)/5,860c
Ranger SuperCab	4.0L V-6	NA/5,740

Ranger SuperCab 4WD	4.0L V-6	3,420(1)/5,580d-e(3)
---------------------	----------	----------------------

(1)=Ranger Edge only(2)=Also available with Tremor(3)=5,160 lb with FX4 Level II;(4)=2,700 lb with FX4 Level II.

Windstar

Windstar Van	3.8L V-6	2,000
Windstar Wagon	3.8L V-6	2,000
Windstar Wagon	3.8L V-6	3,500

* Requires Class II Trailer Tow Package.

TD=Turbodiesel; Ext=Extended cab; NGV=Natural Gas Vehicle; DRW=Dual Rear Wheels; SCC=Super Chassis cab; CCC=Crew Chassis cab.

a=3.08:1 axle ratio;b=3.31:1 axle ratio;c=3.55:1 axle ratio;d=3.73:1 axle ratio;e=4.09/4.10:1 axle ratio=f=4.30:1 axle ratio;g=4.88:1 axle ratio;

h=5.38:1 axle ratio;j=Available in high-altitude areas only;Available with 7,700-Payload Group A only;k=Available with 7,700-Payload Group B only;

l=Must be equipped with heavy-duty towing package;With 16-inch tires or

4! 2 P275 17-inch tires;1=With 4WD P265 or LT265 17-inch tires;2=With

15,000-lb capacity hitch receiver (capacity increase on DRW models effective with fall 2002 production).

The 6.0-liter diesel engine replaces the 7.3-liter Power Stroke diesel engine effective with fall 2002 production. Tow-rating differences between the two engines are within 100 lb on trucks; there are no differences on Excursion models.

Honda

Vehicle	Engine	Tow Limit (lb)
Odyssey	V-6 24-valve	3,500
Pilot	3.5L V-6	3,500a,b

a=With transmission fluid and power-steering fluid coolers and two occupants.

Deduct 150 pounds per passenger, up to seven passengers, without transmission fluid/power-steering fluid coolers: 2,000 lb maximum with two occupants;b=Requires load-leveling hitch.

Hummer

Vehicle	Engine	Tow Limit (lb)
Hummer H1 4dr Open Top	6.5L TD	8,050
Hummer H1 Station Wagon	6.5L TD	7,710
Hummer H2	6.0L V-8	6,700

TD=Turbodiesel

Hyundai

Vehicle	Engine	Tow Limit (lb)
Santa Fe 2WD	2.7L V-6	2,700
Santa Fe 4WD	2.7L V-6	2,280

a=Trailer must be equipped with brakes.

Infinity

Vehicle	Engine	Tow Limit (lb)
QX4	3.5L V-6	5,000

Isuzu

Vehicle	Engine	Tow Limit (lb)
Rodeo/Rodeo Sport	2.2L	2,500
Rodeo Sport	3.2L V-6	4,500
Rodeo	3.2L V-6	4,500
Ascender	4.2L I-6	5,300
Ascender	5.3L V-8	7,000
Axiom	3.5L V-6	4,500 ^a

a=Trailer brakes required on any trailer heavier than 3500 lb.

Jeep

Vehicle	Engine	Tow Limit (lb)
Grand Cherokee	4.0L I-6	5,000
Grand Cherokee	4.7L V-8	6,500
Liberty	2.4L I-4	2000
Liberty	3.7L V-6	5,000 ^{a,b}
Wrangler	2.5L I-4	2,000 ^a
Wrangler	4.0L I-6	2,000

Note: Trailer brakes required on all trailers weighing more than 1,000 lb.

^a=Requires trailer towing package; ^b=Manual-transmission version tows 1,500 lb less.

Kia

Vehicle	Engine	Tow Limit (lb)
Sedona	3.5L V-6	3,500
Sorento	3.5L V-6	3,500

Land Rover

Vehicle	Engine	Tow Limit (lb)
Discovery 4.6L	All	5,500
Range Rover	4.4L V-8	7,700
Freelander	2.5L V-6	2,500

^a=Maximum trailer weight without brakes is 1,650 lb; ^b=Off-road maximum is 2,200 lb.

Lexus

Vehicle	Engine	Tow Limit (lb)
GX 470	4.7L V-8	5,000
LX 470	4.7L V-8	5,000
RX 300	3.0L V-6	5,000

Lincoln

Vehicle	Engine	Tow Limit (lb)
Aviator 2WD/AWD	4.6L V-8	7,300/7,100
Navigator 2WD/4WD	5.4L V-8	8,500/8,300 ^a

^a=Requires optional Class III/IV Trailer Tow Package with load-equalizing hitch

^b=4WD tow rating is 8,300 lb.

Mazda

Vehicle	Engine	Tow Limit (lb)
B2300	2.3L I-4	2,240 [*]
B3000 Reg. Cab	3.0L V-6	2,540
B3000 Reg. Cab	3.0L V-6	4,000
B3000 Cab Plus	3.0L V-6	2,340 [*]
B3000 Cab Plus	3.0L V-6	3,800
B3000 Cab Plus 4WD	3.0L V-6	2,160 [*]
B3000 Cab Plus 4WD	3.0L V-6	3,620
B4000	4.0L V-6	3,280 ^m
B4000	4.0L V-6	5,740
B4000 4WD	4.0L V-6	3,040 ^m
B4000 4WD	4.0L V-6	5,500
Tribute	3.0L V-6	3,500

^a=Automatic transmission; ^m=Manual transmission; ^{*}Manual version tows less than 2,000 lb; ^bRating same for Cab Plus 4 models; ^c=Requires towing package.

Mercedes-Benz

Vehicle	Engine	Tow Limit (lb)
G500	5.0 V-8	7,000
G55AMG	5.5 V-8	7,000
ML320	3.2 V-6	5,000
ML500	5.0 V-8	5,000
ML55AMG	5.5 V-8	5,000

Mercury

Vehicle	Engine	Tow Limit (lb)
Mountaineer #2	4.0L V-6	3,160 ^a
Mountaineer #2	4.0L V-6	5,680
Mountaineer #2	4.6L V-8	3,160 ^a
Mountaineer #2	4.6L V-8	7,040
Mountaineer AWD	4.0L V-6	3,300
Mountaineer AWD	4.0L V-6	5,280
Mountaineer AWD	4.6L V-8	3,300
Mountaineer AWD	4.6L V-8	6,880

^a=With class 2 hitch and standard 3.55 gearing; ^bWith optional class 3 or 4 hitch and 3.73 gearing.

Mitsubishi

Vehicle	Engine	Tow Limit (lb)
Montero	All	5,000 ^a

^a=Tow rating with trailer brakes; 1,500 lb maximum rating without.

Nissan

Vehicle	Engine	Tow Limit (lb)
Frontier	I-4	3,000 ^{a,c}
Frontier	3.3L V-6	2,000 ^{b,c}
Frontier 4WD	3.3L V-6 SC	5,000 ^{c*}
Murano	3.5L V-6	TBD

Pathfinder	3.5L V-6	5,000 ^c
Pathfinder	3.5L V-6	3,500 ^c
Xterra	I-4	3,500 ^{a,c}
Xterra	3.3L V-6	5,000 ^c
Xterra	3.3L V-6 SC	3,500 ^c

a=Manual transmission; b=Automatic transmission; c=Requires factory wiring harness; TBD= To be determined; d=Supercharged, crew cab and longbed models are rated to tow 4,902 lb. Manual-transmission models are rated to tow 3,500 lb, except supercharged, crew cab and longbed models, which are rated to tow 100 lb less

Oldsmobile

Vehicle	Engine	Tow Limit (lb)
Bravada 2WD	4.2L I-6	5,300
Bravada 2WD	4.2L I-6	5,800
Bravada 2WD	4.2L I-6	6,300
Bravada 4WD/AWD	4.2L I-6	5,200
Bravada 4WD/AWD	4.2L I-6	5,700
Bravada 4WD/AWD	4.2L I-6	6,200
Silhouette	3.4L V-6	3,500

a=3.42:1 axle ratio; b=3.73:1 axle ratio; c=4.10:1 axle ratio; d=Requires towing package.

Pontiac

Vehicle	Engine	Tow Limit (lb)
Aztek	3.4L V-6	3,500
Montana	3.4L V-6	3,500

a=Requires towing package.

Porsche

Vehicle	Engine	Tow Limit (lb)
Cayenne	4.5L V-8	7,700

Saturn

Vehicle	Engine	Tow Limit (lb)
VUE AWD	3.0L V-6	2,500

Subaru

Vehicle	Engine	Tow Limit (lb)
Baja	2.5L Flat 4	2,400
Legacy/Outback/Forester	2.5L Flat 4	2,600

a=Trailer brakes required. Maximum hitch weight 200 lb.

Toyota

Vehicle	Engine	Tow Limit (lb)
4Runner	3.4L V-6	5,000
Camry/Avalon	All	2,000
Land Cruiser	4.7L V-8	6,500
Sienna	3.0L V-6	3,500

Tacoma	All I-4	3,500
Tacoma	3.4L V-6	5,000
S-Runner	3.4L V-6	3,500
Sequoia	4.7L V-8	6,500
Sequoia 4WD	4.7L V-8	6,200
Highlander	All I-4	3,000
Highlander	3.0L V-6	3,500
Tundra 4 2 B-Cab	3.4L V-6	5,000
Tundra 4 2 C-Cab	3.4L V-6	4,800
Tundra 4WD C-Cab	3.4L V-6	4,800
Tundra 4 2 C-Cab (SR5, LTD)	4.7L V-8	7,100
Tundra 4WD B-Cab	4.7L V-8	7,200
Tundra 4WD C-Cab (SR5, LTD)	4.7L V-8	6,900

Note: All vehicles hitch weight is 10% of maximum-towing capacity.

* Optional towing package required.

Volkswagen

Vehicle	Engine	Tow Limit (lb)
Eurovan	2.8 V-6	4,400

a=With trailer brakes. Limit for trailer without brakes is 2,200 lb.

Volvo

Vehicle	Engine	Tow Limit (lb)
XC90	2.5L I-5/2.9L I-6	5,000